




# TS100

BOLTLESS  
SEAMING  
SYSTEM




**WE GOT YOU  
COVERED**

TS100 Boltless Seaming System have a sleek design that has no fastening bolt visible on the roof surface. This roof provides total protection. It is designed especially for large industrial and commercial projects. It's profile height and large water carrying capacity enables the roof to have large span capability which translates to fewer purlins and lower cost.

TS100 roof retains high performing installation and strongest water resistant, while having effective width up to 650 mm, TS100 roof reduces both material quantity and construction period.

TS100 is available in ZincAlume and color finishes. With our latest mobile roofing mill, we can rollform on project sites.

# TS100 SPECIFICATIONS




## LENGTHS :

Mobile Rolled on Site to  
custom cut at Site and  
Factory sheet cut

## TOLERANCES :

Length :  $\pm 15\text{mm}$   
Width :  $\pm 4\text{mm}$



Keep your weight evenly distributed over the soles of both feet to avoid concentrating your weight on either heels or toes. Always wear smooth soft-soled shoes; avoid ribbed soles that pick up and hold small stones, swarf and other objects.

Be careful when moving between supports. Do not walk in the pan immediately adjacent to flashings or translucent sheeting. Walk at least one pan away.

## LOAD SPAN

Thickness	Load on Span (Kg/M <sup>2</sup> at Continuous Support)					
	1.25m	1.50m	1.75m	2.00m	2.25m	2.50m
mm(tct)	1.25m	1.50m	1.75m	2.00m	2.25m	2.50m
0,50	495	422	389	351	290	238
0,60	556	501	479	427	332	289

Make allowance for thermal expansion or contraction for long length roofs at sheeting ends.

The equation  $\Delta L = \alpha \times \Delta T \times L$  gives an indication of the sheeting extent or contraction ( $\Delta L$ ).

$\alpha = 12 \times 10^{-6}$  (coefficient of linear expansion for steel)

$\Delta T$  = temperature change in °C  
L = sheet length in mm

## SECTIONAL PROPERTIES

Thickness	Unit Weight		Moment of Inertia	Section Modulus
mm(tct)	Kg/m <sup>2</sup>	Kg/m <sup>2</sup>	Lx = cm <sup>4</sup> /M	Zx = cm <sup>3</sup> /M
0,50	3,38	5,23	108,64	32,88
0,60	4,10	6,30	132,78	40,18

PEAK RAINFALL		ROOF SLOPE (DEGREE)				
Intensity (mm/hour)		1°	2°	3°	5°	8°
100		273	386	473	611	773
150		182	258	315	407	515
200		137	193	237	305	386
250		182	155	189	244	309
300		91	129	158	204	258
400		68	97	118	153	193
500		55	77	95	122	155


Note : Depth of flow in pan has taken into account freeboard allowance (20% of Rib height)

## WATERTIGHT GUARANTEE


An average of 6,000 M2 screw fix roof will have about 30,000 screw holes. Each one a possible source of leakage and corrosion over time period.

Full width and heavy duty TS100 Roof connectors provide incredible holding strength and stability without puncturing the roof sheet.

# DETAILS



# INSTALLATION



All flat metal surfaces can display waviness commonly referred to as "oil canning" is an inherent characteristics of steel product, not a defect, and therefore is not a cause for panel rejection.

## OIL CANNING



PT. TAKUMI AGUNG ABADI  
Kompleks Gading Bukit Indah Blok K 05-06  
Kelapa Gading Permai  
Jakarta 14240

Telp. 021 - 2245 2161  
Fax. 021 - 4585 2631  
Email. pt.takumi.aa@gmail.com